



Jining Jinjia Hydraulic Co., Ltd.



FYRP 2.3/16 H-3 Bearing 2D drawings and 3D CAD models

SKF FYRP 2.3/16 H-3 Flange Block Bearings

Bearing No. FYRP 2.3/16 H-3

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	4.5
EAN	7316576664786
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Round Flange Cartridge
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	22211
Seals	Garter Spring
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch - Metric	Inch
Long Description	4 Bolt Round Flange Cartridge; 2-3/16" Bore; 5.9" Bolt Circle; 4.2" Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Spherical Roller Bearing; 3-1/8" Length Thru Bo



Jining Jinjia Hydraulic Co., Ltd.

Other Features	Double Row Heavy Duty Open End With Set Screw
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	FYRP 2.3/16 H-3
Weight / LBS	9.9
D	3.125 Inch 79.38 Millimeter
Bolt Spacing	4.2 Inch 107.5 Millimeter
d	2.188 Inch 55.575 Millimeter
Nominal Bolt Circle Diameter Round	5.9 Inch 150 Millimeter
Cartridge Pilot Depth	1 Inch 25.4 Millimeter
Cartridge Pilot Diameter	5 Inch 127 Millimeter
bore diameter:	2-3/16 in
expansion type:	Non-Expansion Bearing (Fixed)
bolt center-to-center length:	6.0000 in
seal type:	Radial Shaft Seal
bolt circle diameter:	6 in
overall depth:	3-5/16 in
overall length/diameter:	7.1250 in
radial dynamic load capacity:	22400 lb
flange mounting type:	Four-Bolt Piloted
radial static load capacity:	26500 lb
bearing type:	Spherical Roller
operating temperature range:	-5 to +230 ° F



Jining Jinjia Hydraulic Co., Ltd.

housing construction:	Solid Flange Mount
maximum rpm:	1300 RPM
bore type:	Round
finish/coating:	Uncoated
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	222
locking device:	Set Screw