



Jining Jinjia Hydraulic Co., Ltd.



E-TU-TRB-65MM Bearing 2D drawings and 3D CAD models

TIMKEN E-TU-TRB-65MM Take Up Unit Bearings

Bearing No. E-TU-TRB-65MM

Category	Take Up Unit Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	9.53
EAN	0053893549262
Product Group	M06288
Component Description	Take Up Bearing Only
Rolling Element	Tapered Roller Bearing
Housing Style	Unit Only
Mounting Method	Concentric Collar
Compatible Take Up Frame	Not Specified
Adjustment Travel Length	0
Housing Material	Cast Iron
Other Features	Double Row Double Collar Wide Slot Two Lip Seal Electrodeposition Coating With Set Screw
Inch - Metric	Metric
Long Description	Take Up Bearing Only; 65MM Bore; 27MM Slot Width; 130.175MM Slot to Slot Distance; Tapered Roller Bearing; Unit Only; Concentric Collar Mount; Cast Iron Housing Material
Category	Take Up Units
UNSPSC	31171533



Jining Jinjia Hydraulic Co., Ltd.

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Take Up
Manufacturer URL	http://www.timken.com
Weight / LBS	21
Slot to Slot Distance	5.125 Inch 130.175 Millimeter
d	2.559 Inch 65 Millimeter
Slot Width	1.063 Inch 27 Millimeter
Shaft Size	2.559 in
Shaft Size Type	Metric
Weight	21.0 lb
UPC Code	053893549262
Dimension B	4 in
Dimension L	7-13/16 in
Dimension A ₁	1-1/16 in
Dimension L ₃	4-1/2 in
Dimension L ₁	5-1/16 in
Dimension N	1-3/8 in
Dimension L ₂	1-1/16 in
Dimension N ₁	1-1/4 in
Dimension H ₂	4-15/16 in
Dimension N ₂	2-1/2 in
Dimension d ₁	4-1/16 in
Dimension H ₁	5-1/8 in
Dimension H	6 in
Dimension A ₂	2-3/4 in
e	0.40
X (if $F_a/F_r \leq e$)	0.87
Y (if $F_a/F_r \leq e$)	2.17
X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	2.63
K Factor	1.51



Jining Jinjia Hydraulic Co., Ltd.

C_{90} Dynamic Load Rating ¹	11600 lb
C_0 Static Load Rating	54000 lb
F_{a-max} Maximum Permissible Thrust Load ²	3454 lb
F_{r-max} Maximum Allowable Slip Fit Radial Load ³	9500 lb
Max. Speed ⁴	2420 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to conditions of slip fit with set screw mounting or in applications where a large moment loading occur